


高速短型 | 油压缸

- 

型号	活塞面积-押侧 cm ²	活塞面积-拉侧 cm ²	行程 (mm)	最高回转数 min ⁻¹ (r.p.m.)	最高使用压力 MPa(kgf/cm ²)	I kg·m ²	重量 (kg)
RK-75N	44.2	37.1	15	6000	4.0(40)	0.01	2.8
RK-100N	78.5	71.5	20	6000	4.0(40)	0.03	4.3
RK-125N	122.7	113.1	25	6000	4.0(40)	0.05	6.8
RK-150N	176.7	160.8	30	5500	4.0(40)	0.09	9.4
RK-200N	314.1	290.4	35	5500	4.0(40)	0.28	15.3
RK-250N	469.1	436	60	2000	5.0(50)	0.4	45.2

Technical drawing of the RK-75N/38 pressure washer, showing dimensions and components.

Top View Dimensions:

- Overall width: 70
- Model designation: (RK-75N:60)

Side View Dimensions:

- Trigger gun height: 42
- Trigger gun width: 6~L1
- Trigger gun length: 77.5(RK-250N:90)
- Trigger gun diameter: ØD1
- Trigger gun diameter: ØD2
- Trigger gun diameter: ØC
- Trigger gun diameter: ØF
- Trigger gun diameter: ØE
- Trigger gun diameter: ØM
- Trigger gun diameter: N1
- Trigger gun diameter: N
- Trigger gun diameter: K
- Trigger gun diameter: F
- Trigger gun diameter: E
- Trigger gun diameter: L2
- Trigger gun diameter: L
- Trigger gun diameter: G
- Trigger gun diameter: 5
- Trigger gun diameter: J
- Trigger gun diameter: H

Component Labels:

- RC1/4" Drain Port 浅油孔
- 2~RC3/8"(RK-200N:RC1/2") Pressure Port 給油孔

Legend:

- A: I.D. 内徑
- B: St. 行程

型号	A	B	C	D1	D2	E (h7)	F	G max.	G min.	H	J	K	L	L1	L2	M (H8)	N	NI	P	Q	R	S
RK-75N	75	15	107	90	90	65	30	45	30	57	134.5	M20x2.5	6-M8x16	M8x60	12	21	35	5	28	10	27.5	26
RK-100N	100	20	132	115	100	80	30	45	25	72	149.5	M20x2.5	6-M10x20	M8x75	12	21	35	5	26	10	28.5	32
RK-125N	125	25	160	140	130	110	35	50	25	82	159.5	M24x3.0	6-M12x20	M8x85	12	25	45	5	26	10	28.5	32
RK-150N	150	30	190	170	130	110	45	55	25	95	172.5	M30x3.5	12-M12x24	M10x100	16	32	45	5	26	10	28.5	32
RK-200N	200	35	245	220	145	120	55	70	35	115	192.5	M36x4.0	12-M16x30	M10x125	21	38	60	5	30	6	28.5	28
RK-250N	245	60	307	275	220	160	65	85	25	165	255.0	M42x 3.0	6-M20x2.5	M16x175	28	45	65	12	37	18	6	-