

中实型 | 3爪

-

型号	-	楔心行程 (mm)	爪行程(直径) (mm)	最大夹持直径 (mm)	最小夹持直径 (mm)	容许最大入力 kN (kgf)	最大夹持力 kN (kgf)	最高回转数 min ⁻¹ (r.p.m.)	I kg·m ²	I kg·m ²	重量 (kg)	重量 (kg)	适用回转缸	最大使用压力 MPa(kgf/cm ²)
3V-12	A8	30	12.7	304	30	41.0 (4180)	156 (15900)	3150	0.73	0.79	62.9	68.7	RK-150 RE-150	2.6(26)
3V-15	A8	35	16	381	30	81.9 (8360)	245.1 (25000)	2900	1.97	2.27	105.5	128.5	RK-200 RE-200K	2.8(28) 3.0(30)
3V-15	A11	35	16	381	30	81.9 (8360)	245.1 (25000)	2900	1.97	2.27	105.5	127	RK-200 RE-200K	2.8(28) 3.0(30)
3V-15	A15	35	16	381	30	81.9 (8360)	245.1 (25000)	2900	3.33	2.67	105.5	142	RK-200 RE-200K	2.8(28) 3.0(30)
3V-18	A8	35	16	450	80	81.9 (8360)	245.1 (25000)	2600	3.33	3.62	132.7	155.5	RK-200 RE-200K	2.8(28) 3.0(30)
3V-18	A11	35	16	450	80	81.9 (8360)	245.1 (25000)	2600	3.33	3.63	132.7	154.5	RK-200 RE-200K	2.8(28) 3.0(30)
3V-18	A15	35	16	450	80	81.9 (8360)	245.1 (25000)	2600	6.83	4.02	132.7	165	RK-200 RE-200K	2.8(28) 3.0(30)
3V-21	A11	35	16	530	62	81.9 (8360)	271.6 (27700)	1800	6.83	7.46	196.5	227	RK-200 RE-200K	2.8(28) 3.0(30)
3V-21	A15	35	16	530	62	81.9 (8360)	271.6 (27700)	1800	6.83	7.37	196.5	221	RK-200 RE-200K	2.8(28) 3.0(30)
3V-24	A11	35	16	610	136	81.9 (8360)	271.6 (27700)	1700	11.19	11.83	241.7	272.8	RK-200 RE-200K	2.8(28) 3.0(30)
3V-24	A15	35	16	610	136	81.9 (8360)	271.6 (27700)	1700	11.19	11.73	241.7	266	RK-200 RE-200K	2.8(28) 3.0(30)
3V-32	A15	35	16	800	136	81.9 (8360)	271.6 (27700)	1100	28.97	29.51	353.6	378	RK-200 RE-200K	2.8(28) 3.0(30)
3V-40	A20	57	46+(60)	1005	310	180 (18350)	320 (32620)	630	68	72	780	849	RK-250 RE-250 RE-A250 RE-L250	4.2(42)
3V-50	A20	57	46+(60)	1250	290	180 (18350)	320 (32620)	500	145	148	1000	1050	RK-250 RE-250 RE-A250 RE-L250	4.2(42)
3V-63	-	60	48+(80)	1600	390	200 (20390)	360 (36700)	400	500	-	1600	-	RK-250 RE-250 RE-A250 RE-L250	4.6(46)
3V-79	-	60	48+(80)	2000	440	200 (20390)	360 (36700)	320	1250	-	2500	-	RK-250 RE-250 RE-A250 RE-L250	4.6(46)

尺寸



*紅色數據為 3V-A 型之寸法